

ENGLISH

ULISSE

Complete range for outdoor surveillance



the evolution of the species...



ULISSE COMPLETE RANGE OF INTEGRATED POSITIONING UNITS

ULISSE the positioning unit for dynamic outdoor surveillance. *More than a PTZ, better than a Speed Dome*, this advanced Videotec product integrates a high performances P&T head, telemetry receiver, camera, IP video encoder, illuminators and more.



ULISSE COMPACT

DAY/NIGHT CAMERA INCLUDED. BUILT-IN IR-LED LAMP VERSION



ULISSE COMPACT THERMAL

THERMAL CAMERA AND DAY/NIGHT CAMERA INCLUDED



ULISSE

STANDARD MODEL FOR YOUR CHOICE OF CAMERA AND LENS COMBINATION



ULISSE NETWORK CAM

FOR NETWORK CAMERAS



ULISSE THERMAL

FOR THERMAL CAMERAS



ULISSE IR360

WITH BRACKET FOR TWO INFRARED-LAMPS, 360° CONTINUOUS ROTATION



ULISSE PLUS

WITH LARGER HOUSING



ULISSE MAXI

WITH EXTRA LARGE HOUSING FOR ALMOST ANY CAMERA/LENS COMBINATION

	ULISSE COMPACT		ULISSE COMPACT THERMAL		ULISSE		ULISSE NETWORK CAM		ULISSE THERMAL		ULISSE IR360		ULISSE PLUS		ULISSE MAXI	
VARIABLE SPEED	PAN 0.1°±200°/s	TILT 0.1°±200°/s	PAN 0.1°±200°/s	TILT 0.1°±200°/s	PAN 0.1°±100°/s	TILT 0.1°±40°/s	PAN 0.1°±100°/s	TILT 0.1°±40°/s	PAN 0.1°±100°/s	TILT 0.1°±40°/s	PAN 0.1°±40°/s	TILT 0.1°±30°/s	PAN 0.02°±100°/s	TILT 0.02°±50°/s	PAN 0.1°±20°/s	TILT 0.1°±20°/s
BUILT-IN WIPER	OPTIONAL		YES		OPTIONAL		OPTIONAL		-		OPTIONAL		OPTIONAL		YES	
INTEGRATED DAY/NIGHT CAMERA	36x, 18x, 10x ZOOM		36x ZOOM		OPTIONAL (36x ZOOM)		-		-		OPTIONAL (36x ZOOM)		-		-	
INTEGRATED THERMAL CAMERA	-		UNCOOLED VOx 320x256pixels, <9Hz ¹		-		-		-		-		-		-	
FOR NETWORK CAMERA	-		-		-		YES (CAMERA NOT INCLUDED)		-		-		-		-	
INFRARED ILLUMINATOR	OPTIONAL		-		-		OPTIONAL ²		-		YES ²		OPTIONAL ²		-	
FOR MOTORIZED ZOOM LENSES	-		-		FOR COMPACT-SIZE ZOOM LENSES		FOR COMPACT-SIZE ZOOM LENSES		-		FOR COMPACT-SIZE ZOOM LENSES		FOR MEDIUM-SIZE ZOOM LENSES		FOR LARGE-SIZE ZOOM LENSES	
CAMERA USEFUL AREA	-		-		WxHxL: 80x89x330mm (3.1x3.5x13in)		WxHxL: 80x89x330mm (3.1x3.5x13in)		WxHxL: 80x89x330mm (3.1x3.5x13in)		WxHxL: 80x89x330mm (3.1x3.5x13in)		WxHxL: 100x115x330mm (3.5x4.5x13in)		WxHxL: 152x160x432mm (6x6.3x17in)	
ABSOLUTE POSITIONING (ENCODER)	-		-		OPTIONAL		OPTIONAL		OPTIONAL		-		YES		YES	
IP VIDEO ENCODER	OPTIONAL		-		OPTIONAL		-		OPTIONAL		OPTIONAL		OPTIONAL		OPTIONAL	
INTEGRATED "ALBERT" UNIT FOR VCA	OPTIONAL		-		-		-		-		-		-		-	
PRESET ACCURACY	0.05°		0.05°		0.02°		0.02°		0.02°		0.02°		0.02°		0.02°	
OPERATING TEMPERATURE	MIN -40°C (-40°F)	MAX +60°C (+140°F)	MIN -40°C (-40°F)	MAX +60°C (+140°F)	MIN -20°C (-4°F) ³	MAX +60°C (+140°F)	MIN -20°C (-4°F) ³	MAX +60°C (+140°F)	MIN -20°C (-4°F) ³	MAX +60°C (+140°F)	MIN -20°C (-4°F) ³	MAX +60°C (+140°F)	MIN -20°C (-4°F)	MAX +60°C (+140°F)	MIN -10°C (+14°F)	MAX +60°C (+140°F)

¹ Higher resolution and/or frame rate are available upon request.

² Only support: lamps not included.

³ -30°C (-22°F) with optional cold pack.

ULISSE positioning units are ideal for use in several kinds of outdoor installations, such as: coastal and harbour controls, border patrol, urban settings, highway and traffic monitoring, stadiums and industry, prisons and any applications involving perimeter surveillance.

KEY BENEFITS OF THE ULISSE RANGE



Hi-speed rotation with accurate preset positioning. Precise mechanism for smooth movement.



Capability to watch above horizon so it may be installed on poles lower than those used by speed domes, with a better image quality (less vibrations) and lower costs for installation and maintenance.



Designed to work from extremely cold to extremely hot. sophisticated de-icing functions have been implemented.



Wiper option. Washer pump accessory available for all models.



360° continuous rotation. Zero-back lash mechanism.



Firmware upgradable from remote sites (no need to go on top of the pole to implement the new features added by Videotec).



Illuminator aligned with the camera, giving illumination in the dark without multiple lights.



No blind spots due to mounting brackets (Speed domes when installed on parapets or on poles with a gooseneck mount - typically outdoor - always have a blind spot).



IP66 weatherproof.



ULISSE COMPACT



ULISSE



ULISSE MAXI



HEADQUARTERS ITALY VIDEOTEC S.p.A.

Via Friuli, 6 - I-36015 Schio (VI) Italy
 Tel. +39 0445 697411 - Fax +39 0445 697414
 Email: info@videotec.com

UK/IRELAND SALES REPRESENTATIVE

Tel./Fax +44 01353 775438 (*Sales*)
 Tel. +44 0113 815 0047 (*Technical support*)
 Tel. +44 0113 815 0031 (*Orders/Shipping dept.*)
 Email: uksales@videotec.com

ASIA PACIFIC VIDEOTEC (HK) Ltd

Unit C 24 Floor - Gold King Industrial Building
 35-41, Tai Lin Pai Road - Kwai Chung, NT, Hong Kong
 Tel. +852 2333 0601 - Fax +852 2311 0026
 Email: info@videotec.com.hk

FRANCE VIDEOTEC FRANCE S.à.r.l.

Voie du Futur - Zac des Portes - 27100 Val de Reuil, France
 Tel. +33 2 32094900 - Fax +33 2 32094901
 Email: info@videotec-france.com

AMERICAS VIDEOTEC SECURITY, Inc.

The Lower level South Suite - The Ottilio Office Complex I
 555 Preakness Ave. - Totowa, NJ 07512 - U.S.A.
 Tel. +1 973 5950788 - Fax +1 425 6484289
 Email: usasales@videotec.com - www.videotec.us

www.videotec.com